


20543 公制内螺纹24°锥O型圈重型 45°弯接头

Metric Female Thread 24° Taper O-Ring
Heavy Duty 45° Elbow Coupling

- ISO 8434-1, DIN 3861
- 常规供货碳钢/表面镀锌

- ISO 8434-1, DIN 3861
- General supply carbon steel/surface galvanized

钢管外径	软管内径		尺寸		六角	螺纹	型号	产品编码
D1	D2(DN)	D2(in)	L1	L2	S1	P1	Type	Product Code
25	20	3/4	89.4	33	41	M36x2	20543-36-12	HF22343612
30	25	1	102.3	35.9	50	M42x2	20543-42-16	HF22344216
38	32	1 1/4	114.5	39.4	60	M52x2	20543-52-20	HF22345220



20593 公制内螺纹24°锥O型圈重型90°弯接头

Metric Female Thread 24° Taper O-Ring Heavy Duty 90°
Elbow Coupling

- ISO 8434-1, DIN 3861
- 常规供货碳钢/表面镀锌

- ISO 8434-1, DIN 3861
- General supply carbon steel/galvanized surface

钢管外径	软管内径		尺寸		六角	螺纹	型号	产品编码
D1	D2(DN)	D2(in)	L1	L2	S1	P1	Type	Product Code
25	20	3/4	74.5	67.8	46	M36x2	20593-36-12	HF32343612
25	25	1	88.9	79.5	46	M36x2	20593-36-16	HF32343616
30	25	1	88.9	80.5	50	M42x2	20593-42-16	HF32344216
30	32	1 1/4	105.8	91.5	50	M42x2	20593-42-20	HF32344220
38	32	1 1/4	105.8	86.5	60	M52x2	20593-52-20	HF32345220
38	40	1 1/2	124.2	104.5	60	M52x2	20593-52-24	HF32345224