



GZ 组合接头 Combined connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径	尺寸		六角	螺纹	重量	型号	产品编码
D1	L1	L2	S1	P1	kg/100	Type	Product Code
6	34	36	17	M12x1.5	4.6	GZ06L	BF1200606
8	34	36	17	M14x1.5	4.5	GZ08L	BF1200808
10	36	37	19	M16x1.5	5.5	GZ10L	BF1201010
12	36	37	22	M18x1.5	7.8	GZ12L	BF1201212
15	39	40	27	M22x1.5	12.5	GZ15L	BF1201515
18	40.5	42.5	32	M26x1.5	18.0	GZ18L	BF1201818
22	45	46.5	36	M30x2	25.0	GZ22L	BF1202222
28	47	48.5	46	M36x2	42.5	GZ28L	BF1202828
35	53	57.5	50	M45x2	46.5	GZ35L	BF1203535
42	53	58.5	60	M52x2	69.5	GZ42L	BF1204242
6	37	39	17	M14x1.5	4.5	GZ06S	BF1700606
8	37	39	19	M16x1.5	6.5	GZ08S	BF1700808
10	41	43	22	M18x1.5	8.5	GZ10S	BF1701010
12	42	44	24	M20x1.5	11.0	GZ12S	BF1701212
14	45	48	27	M22x1.5	14.2	GZ14S	BF1701414
16	46	50	30	M24x1.5	18.0	GZ16S	BF1701616
20	55	59.5	36	M30x2	29.5	GZ20S	BF1702020
25	58	65.5	46	M36x2	51.3	GZ25S	BF1702525
30	62	72.5	50	M42x2	63.5	GZ30S	BF1703030
38	67	82.5	60	M52x2	91.0	GZ38S	BF1703838