



GAI-R 直通内螺纹接头 Straight female thread connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸		六角	螺纹		重量	型号	产品编码
D1	L1	L2	L3	S1	P1	P2	kg/100	Type	Product Code
6	7	12	26	14	M12x1.5	G1/8	1.9	GAI06LR	BF1140602
8	7	17	31	19	M14x1.5	G1/4	3.8	GAI08LR	BF1140804
10	8	17	32	19	M16x1.5	G1/4	3.9	GAI10LR	BF1141004
12	9	17	33	24	M18x1.5	G3/8	6.2	GAI12LR	BF1141206
15	11	20	28	30	M22x1.5	G1/2	8.6	GAI15LR	BF1141508
18	10.5	20	28	27	M26x1.5	G1/2	8.9	GAI18LR	BF1140808
22	13.5	22	43	36	M30x2	G3/4	8.9	GAI22LR	BF1142212
28	13.5	24.5	45.5	41	M36x2	G1	20.6	GAI28LR	BF1142816
35	14.5	26.5	51.5	55	M45x2	G1 1/4	46.3	GAI35LR	BF1143520
42	14	28.5	53.5	60	M52x2	G1 1/2	52.8	GAI42LR	BF1144224
6	9	17	33	19	M14x1.5	G1/4	4.2	GAI06SR	BF1640604
8	9	17	33	19	M16x1.5	G1/4	4.4	GAI08SR	BF1640804
10	9.5	17	34	24	M18x1.5	G3/8	6.9	GAI10SR	BF1641006
12	9.5	17	34	24	M20x1.5	G3/8	7.2	GAI12SR	BF1641206
14	12	20	40	27	M22x1.5	G1/2	9.7	GAI14SR	BF1641408
16	11.5	20	40	30	M24x1.5	G1/2	9.4	GAI16SR	BF1641608
20	12.5	24.5	45	36	M30x2	G3/4	19.3	GAI20SR	BF1642012
25	13	26.5	49.5	41	M36x2	G1	24.2	GAI25SR	BF1642516
30	15.5	28.5	55.5	55	M42x2	G1 1/4	50.1	GAI30SR	BF1643020
38	15	15	59.5	60	M52x2	G1 1/2	58.4	GAI38SR	BF1643824