


SKAR


变径接管焊接接头

Reducing pipe welding connector



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径		尺寸			重量	型号	产品编码
D1	D2	L1	L2	L3	kg/100	Type	Product Code
8	6	31	12	3	1.4	SKAR08/06X1.5	BF9080806
10	8	32.5	12	5	1.6	SKAR10/08X1.5	BF9081008
10	8	32.5	12	4	1.7	SKAR10/08X2	BF9021008
12	8	32.5	14	5	1.8	SKAR12/08X1.5	BF9081208
12	10	32.5	14	7	1.8	SKAR12/10X1.5	BF9081210
16	10	39	15	6	4.3	SKAR16/10X2	BF9021610
16	12	39	15	9	4.5	SKAR16/12X1.5	BF9081612
16	12	39	15	8	4.7	SKAR16/12X2	BF9021612
16	12	39	15	7	4.9	SKAR16/12X2.5	BF9091612
20	12	45	17	9	7.6	SKAR20/12X1.5	BF9082012
20	12	45	17	8	7.8	SKAR20/12X2	BF9022012
20	12	45	17	7	8.0	SKAR20/12X2.5	BF9092012
20	12	45	17	6	8.6	SKAR20/12X3	BF9032012
20	16	45	17	12	7.4	SKAR20/16X2	BF9022016
20	16	45	17	11	7.6	SKAR20/16X2.5	BF9092016
20	16	45	17	10	7.8	SKAR20/16X3	BF9032016
25	12	49.5	20	9	11.7	SKAR25/12X1.5	BF9082512
25	12	49.5	20	8	12.1	SKAR25/12X2	BF9022512
25	12	49.5	20	7	12.5	SKAR25/12X2.5	BF9092512
25	16	49.5	20	12	11.5	SKAR25/16X2	BF9022516
25	16	49.5	20	11	12.0	SKAR25/16X2.5	BF9092516
25	16	49.5	20	10	12.3	SKAR25/16X3	BF9032516
25	20	49.5	20	16	9.4	SKAR25/20X2	BF9022520
25	20	49.5	20	15	10.4	SKAR25/20X2.5	BF9092520
25	20	49.5	20	14	11.4	SKAR25/20X3	BF9032520
25	20	49.5	20	12	12.4	SKAR25/20X4	BF9042520



SKAR

变径接管焊接接头

Reducing pipe welding connector


- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径		尺寸			重量	型号	产品编码
D1	D2	L1	L2	L3	kg/100	Type	Product Code
30	16	52	22	12	16.6	SKAR30/16X2	BF9023016
30	16	52	22	11	17.6	SKAR30/16X2.5	BF9093016
30	20	52	22	16	14.9	SKAR30/20X2	BF9023020
30	20	52	22	15	15.9	SKAR30/20X2.5	BF9093020
30	20	52	22	14	16.9	SKAR30/20X3	BF9033020
30	20	52	22	12	18.4	SKAR30/20X4	BF9043020
30	25	52	22	20	14.1	SKAR30/25X2.5	BF9093025
30	25	52	22	19	15.6	SKAR30/25X3	BF9033025
30	25	52	22	17	16.8	SKAR30/25X4	BF9043025
38	16	56.5	26	12	27.9	SKAR38/16X2	BF9023816
38	16	56.5	26	11	29.4	SKAR38/16X2.5	BF9093816
38	16	56.5	26	10	30.9	SKAR38/16X3	BF9033816
38	20	56.5	26	16	26.3	SKAR38/20X2	BF9023820
38	20	56.5	26	15	27.8	SKAR38/20X2.5	BF9093820
38	20	56.5	26	14	29.3	SKAR38/20X3	BF9033820
38	20	56.5	26	12	29.9	SKAR38/20X4	BF9043820
38	25	56.5	26	20	24.2	SKAR38/25X2.5	BF9093825
38	25	56.5	26	19	26.2	SKAR38/25X3	BF9033825
38	30	56.5	26	24	25.6	SKAR38/30X3	BF9033830
38	30	56.5	26	22	28.6	SKAR38/30X4	BF9043830
38	30	56.5	26	20	31.6	SKAR38/30X5	BF9053830

SKAR

变径接管焊接接头

Reducing pipe welding connector



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径		尺寸			重量	型号	产品编码
D1	D2	L1	L2	L3	kg/100	Type	Product Code
10	6	32.5	12	3	1.5	SKAR10/06X1.5	BF9081006
12	8	32.5	14	4	2.0	SKAR12/08X2	BF9021208
25	12	49.5	20	6	12.9	SKAR25/12X3	BF9032512
30	12	52	22	9	13.5	SKAR30/12X1.5	BF9083012
30	12	52	22	8	14.5	SKAR30/12X2	BF9023012
30	12	52	22	6	15.5	SKAR30/12X3	BF9033012
38	12	56.5	26	9	21.9	SKAR38/12X1.5	BF9083812
38	12	56.5	26	8	23.4	SKAR38/12X2	BF9023812
38	12	56.5	26	6	24.9	SKAR38/12X3	BF9033812
38	25	56.5	26	17	28.5	SKAR38/25X4	BF9043825