



EGE-R-ED

端直通组合接头

Straight-through combination connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径	尺寸		六角		螺纹		重量	型号	产品编码
D1	L1	L2	S1	S2	P1	P2	kg/100	Type	Product Code
6	8	24.5	14	17	M12x1.5	G1/8A	3.6	EGE06LRED	BF1220602
8	12	29.5	19	17	M14x1.5	G1/4A	5.7	EGE08LRED	BF1220804
10	12	27.5	19	19	M16x1.5	G1/4A	5.8	EGE10LRED	BF1221004
12	12	27.5	19	22	M18x1.5	G1/4A	6.8	EGE12LR1/4ED	BF1221204
12	12	34	22	22	M18x1.5	G3/8A	7.5	EGE12LRED	BF1221206
15	14	32	27	27	M22x1.5	G1/2A	14.4	EGE15LRED	BF1221508
18	14	31.5	27	32	M26x1.5	G1/2A	15.2	EGE18LRED	BF1221808
22	16	32.5	32	36	M30x2	G3/4A	20.2	EGE22LRED	BF1222212
28	18	35	41	46	M36x2	G1A	35.6	EGE28LRED	BF1222816
35	20	42.5	50	50	M45x2	G1 1/4A	50.7	EGE35LRED	BF1222520
42	22	46.5	55	60	M52x2	G1 1/2A	66.4	EGE42LRED	BF1224224
6	12	27	19	17	M14x1.5	G1/4A	5.6	EGE06SRRED	BF1720604
8	12	29.5	19	19	M16x1.5	G1/4A	6.2	EGE08SRRED	BF1720804
10	12	32	22	22	M18x1.5	G3/8A	9.2	EGE10SRRED	BF1721006
12	12	34	22	24	M20x1.5	G3/8A	11.0	EGE12SRRED	BF1721206
12	14	34.5	27	24	M20x1.5	G1/2A	15.3	EGE12SR1/2ED	BF1721208
14	14	36.5	27	27	M22x1.5	G1/2A	17.0	EGE14SRRED	BF1721408
16	14	37	27	30	M24x1.5	G1/2A	23.0	EGE16SRRED	BF1721608
20	16	43	32	36	M30x2	G3/4A	28.6	EGE20SRRED	BF1722012
25	18	48	41	46	M36x2	G1A	49.4	EGE25SRRED	BF1722516
30	20	51	50	50	M42x2	G1 1/4A	67.4	EGE30SRRED	BF1723020
38	22	60	55	60	M52x2	G1 1/2A	93.0	EGE38SRRED	BF1723824