


20SF AW 气动快换-公头

Pneumatic quick change-male



- 口径 $2,7=6\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度：
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $2,7=6\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)


尺寸		六角	螺纹	型号	产品编码
L1	L2	S1	P1	Type	Product Code
5	18	7	M5	20SFAW05 MXX	QC93000007
				20SFAW05 MXN	QC93000008
7	20	11	G1/8	20SFAW10 MXX	QC93000009
				20SFAW10 MXN	QC93000010

注：MXX为标准，MXN为镀镍

Note: MXX is standard, MXN is nickel-plated

20SB AW 气动快换-公头

Pneumatic quick change-male



- 口径 $2,7=5\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度：
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $2,7=5\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

尺寸		六角	螺纹	型号	产品编码
L1	L2	S1	P1	Type	Product Code
5	28	9	M5	20SB AW05 MPX	QC93000011
				20SB AW05 MPN	QC93000012
7	30	11	G1/8	20SB AW10 MPX	QC93000013
				20SB AW10 MPN	QC93000014

注：MPX为标准，MPN为镀镍

Note: MPX is standard, MPN is nickel-plated