


21KB KO 气动快换-母头

Pneumatic quick change-female

- 材料:聚甲醛 (POM) 和聚偏氟乙烯 (PVDF)
- 通径5=20mm
- 常用于小型气动、医疗、化学和制药行业
- 工作压力PB=10bar (POM)
PB=8bar (PVDF)
- 适用温度: -20°C~+80°C (POM)
-20°C~+120°C (PVDF)

- Materials: polyoxymethylene (POM) and polyvinylidene fluoride (PVDF)
- Diameter 5 = 20mm²
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure PB = 10bar (POM)
PB = 8bar (PVDF)
- Applicable temperature: -20°C ~ +80°C (POM)
-20°C ~ +120°C (PVDF)

尺寸		六角	螺纹	型号	产品编码
L1	L2	S1	P1	Type	Product Code
				21KB KO08 FVX	QC96000027



20SF KO 气动快换-公头

Pneumatic quick change-male

- 通径2,7=6mm²
- 常用于小型气动、医疗、化学和制药行业
- 工作压力PB=35bar
- 适用温度:
-20°C~+100°C (NBR)
-40°C~+120°C (EPDM)
-15°C~+200°C (FKM)

- Orifice 2,7=6mm²
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure PB=35bar
- Applicable temperature:
-20°C~+100°C (NBR)
-40°C~+120°C (EPDM)
-15°C~+200°C (FKM)

尺寸		六角	螺纹	型号	产品编码
L1	L2	S1	P1	Type	Product Code
3x4mm		7	M7x0.5	20SF KO04 MXX	QC93000001
				20SF KO04 MXN	QC93000002
3x5mm		7	M7x0.5	20SF KO05 MXX	QC93000003
				20SF KO05 MXN	QC93000004
4x6mm		8	M8x0.5	20SF KO06 MXX	QC93000005
				20SF KO06 MXN	QC93000006

注: MXX为标准, MXN为镀镍

Note: MXX is standard, MXN is nickel-plated