


WV

三通梭阀

Three-way shuttle valve



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌
- 温度: -40°C~+120°C
- 泄漏: 最高压力下每分钟20滴
- 不与焊接接管和旋转螺母连接
- 介质从右进口进入时, 浮动钢球在介质动力作用下, 自动将左进口关闭

- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/surface galvanized
- Temperature: -40°C~+120°C
- Leakage: 20 drops per minute at maximum pressure
- Not connected with welding pipe and rotating nut
- When the medium enters from the right inlet, the floating steel ball automatically closes the left inlet under the power of the medium

钢管外径		尺寸		六角	螺纹	工作压力	重量	型号	产品编码
D1	D2	L1	L2	S1	P1	Mpa	kg/100	Type	Product Code
8	4.5	21	14	14	M14x1.4	16	5.3	WV08L	BV5000808
10	6	22	15	17	M16x1.5	16	7.3	WV10L	BV5001010
12	7.5	24	17	19	N18x1.5	16	9.6	WV12L	BV5001212
15	10	28	21	19	M22x1.5	16	13.4	WV15L	BV5001515