

12EU-树脂管

Resin tube



- 软管结构: 一/二层高抗拉棉丝编织层, 聚脂系热塑弹性体内层, 聚胺脂材料外层。
- 应用: 一般液压系统, 液压吊臂, 液压传动材料。
- 适配接头: 两件式编织类扣压接头
- SAE 100R7
- 温度范围: -40°C~+100°C

- Hose structure: one or two layers of high tensile cotton braided layer, polyester thermoplastic elastomer inner layer, polyurethane outer layer.
- Application: general hydraulic system, hydraulic boom, hydraulic transmission material.
- Adapter: two-piece braided crimping connector
- SAE 100R7
- Temperature range: -40°C~+100°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
5	3/16	4.8	10.3	23.0	80	45	0.07	12EU 338-05	SH120705
6	1/4	6.3	11.5	23.0	80	50	0.09	12EU 338-06	SH120706
8	5/16	7.9	14.2	23.0	80	60	0.14	12EU 338-08	SH120708
10	3/8	9.6	16.2	23.0	80	80	0.14	12EU 338-10	SH120710
12	1/2	12.7	22.0	20.0	60	100	0.19	12EU 338-13	SH120713
16	5/8	15.9	25.6	15.0	40	160	0.23	12EU 338-16	SH120716
20	3/4	19.0	26.4	10.0	35	254	0.25	12EU 338-19	SH120719

13EU-树脂管

Resin tube



- 软管结构: 一层高芳纶纤维编织层, 聚脂系热塑弹性体内层, 高耐磨聚胺脂材料外层。
- 应用: 一般高压液压系统, 输送液压油、气体, 适用于升降铲车、吊臂, 农业器材和液压传动器材。
- 适配接头: 两件式编织类扣压接头
- SAE 100R8
- 温度范围: -40°C~+80°C

- Hose structure: one layer of high aramid fiber braided layer, polyester thermoplastic elastomer inner layer, high wear-resistant polyurethane outer layer.
- Application: general high-pressure hydraulic system, conveying hydraulic oil and gas, suitable for lifting forklifts, booms, agricultural equipment and hydraulic transmission equipment.
- Adapter: two-piece braided crimping connector
- SAE 100R8
- Temperature range: -40°C~+80°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
5	3/16	4.8	10.4	34.5	138	50	0.07	13EU 001-05	SH130805
6	1/4	6.3	12.7	34.5	138	50	0.10	13EU 001-06	SH130806
8	5/16	7.9	13.6	29.5	118	60	0.13	13EU 001-08	SH130808
10	3/8	9.6	16.3	27.6	110	63	0.14	13EU 001-10	SH130810
12	1/2	12.8	19.3	24.1	96.5	100	0.19	13EU 001-13	SH130813
16	5/8	15.9	23.1	19.0	76	203	0.23	13EU 001-16	SH130816
20	3/4	18.9	27.9	15.5	62	254	0.26	13EU 001-19	SH130819
25	1	25.4	35.8	11.2	55	305	0.36	13EU 001-25	SH130825