



EFG5K-液压软管

Hydraulic hose

- 软管结构: 四层高强度钢丝缠绕层, 耐油丁腈橡胶内层, 耐油耐磨黑色合成橡胶外层。
- 应用: 极端高压液压应用。
- 适配接头: 一体式或两件式扣压接头
- 温度范围: -40°C~+121°C

							#	产品编码
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
10	3/8	9.5	20.3	34.5	64		EFG5K-06	HH140506
12	1/2	12.7	24.1	34.5	89		EFG5K-08	HH140508
16	5/8	15.9	27.7	34.5	102		EFG5K-10	HH140510
20	3/4	19.1	31.5	34.5	122		EFG5K-12	HH140512
25	1	25.4	38.9	34.5	152		EFG5K-16	HH140516
32	1 1/4	31.8	50.0	34.5	211		EFG5K-20	HH140520
40	1 1/2	38.1	57.4	34.5	254		EFG5K-24	HH140524
50	2	50.8	71.1	34.5	635		EFG5K-32	HH140532
64	2 1/2	63.5	85.1	34.5	762		EFG5K-40	HH140540

注: 公称内径32为六层高强度钢丝缠绕。

Note: Nominal inner diameter 32 is wound with six layers of high-strength steel wire.



EFG6K-液压软管

Hydraulic hose

- 软管结构: 四层高强度钢丝缠绕层, 耐油丁腈橡胶内层, 耐油耐磨黑色合成橡胶外层。
- 应用: 极端高压、高脉冲应用。
- 适配接头: 一体式或两件式扣压接头
- SAE 100R15
- 温度范围: -40°C~+121°C

							#	产品编码
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
10	3/8	9.5	20.3	41.4	64		EFG6K-06	HH140606
12	1/2	12.7	24.1	41.4	89		EFG6K-08	HH140608
16	5/8	15.9	27.7	41.4	102		EFG6K-10	HH140610
20	3/4	19.1	31.5	41.4	122		EFG6K-12	HH140612
25	1	25.4	38.9	41.4	152		EFG6K-16	HH140616
32	1 1/4	31.8	50.0	41.4	208		EFG6K-20	HH140620
40	1 1/2	38.1	57.4	41.4	254		EFG6K-24	HH140624

注: 公称内径32为六层高强度钢丝缠绕。

Note: Nominal inner diameter 32 is wound with six layers of high-strength steel wire.