

FC300-燃油管

Fuel pipe



- 软管结构: 一层涤纶编织层, 一层钢丝编织增强层, AQP弹性体内层, 蓝色聚酯编织外层。
- 应用: 适用石油基液压油、空气、汽油、燃油、润滑油、耐燃液压油或其他工业液压油的液压系统。
- 适配接头: 一体式或两件式, 编织类扣压接头, R5可拆式接头
- SAE 100 R5
- 温度范围: -49°C~+150°C
- 空气最高温度: 121°C
- Hose structure: one polyester braided layer, one steel wire braided reinforcement layer, AQP elastomer inner layer, blue polyester braided outer layer.
- Application: Suitable for hydraulic systems with petroleum-based hydraulic oil, air, gasoline, fuel oil, lubricating oil, flame-resistant hydraulic oil or other industrial hydraulic oil.
- Adapter: one-piece or two-piece, braided crimping connector, R5 detachable connector
- SAE 100 R5
- Temperature range: -49°C~+150°C
- Maximum air temperature: 121°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
5	0.19	4.8	13.2	21.0	84.0	76.2	0.19	FC300-04	SH030004
6	0.25	6.4	14.7	21.0	84.0	85.9	0.24	FC300-05	SH030005
8	0.31	7.9	17.3	15.7	63.0	101.6	0.27	FC300-06	SH030006
11	0.41	10.4	19.6	14.0	56.0	117.3	0.32	FC300-08	SH030008
12	0.50	12.7	23.4	12.2	49.0	139.7	0.49	FC300-10	SH030010
16	0.63	16.0	27.4	10.5	42.0	165.1	0.58	FC300-12	SH030012
22	0.88	22.4	31.2	5.6	22.4	187.5	0.55	FC300-16	SH030016
29	1.12	28.4	38.1	4.3	17.5	228.6	0.68	FC300-20	DH030020
35	1.38	35.1	44.5	3.5	14.0	266.7	0.92	FC300-24	SH030024
46	1.81	46.0	56.4	2.1	8.4	336.6	1.28	FC300-32	SH030032
60	2.38	60.1	73.2	2.1	8.4	609.6	2.11	FC300-40	SH030040

FC350-燃油管

Fuel pipe



- 软管结构: 一层聚酯编织层, 一层钢丝编织增强层, AQP弹性体内层, 黑色涤纶编织外层。
- 应用: 适用于空气、汽油、燃油、润滑油和冷却剂。
- 适配接头: 一体式或两件式, 编织类扣压接头, R5可拆式接头
- 温度范围: -49°C~+150°C
- 空气最高温度: 121°C
- Hose structure: one polyester braided layer, one steel wire braided reinforcement layer, AQP elastomer inner layer, black polyester braided outer layer.
- Application: suitable for air, gasoline, fuel, lubricating oil and coolant.
- Adapter: one-piece or two-piece, braided crimping connector, R5 detachable connector
- Temperature range: -49°C~+150°C
- Maximum air temperature: 121°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
5	0.19	4.8	13.2	14.0	56.0	19.1	0.22	FC350-04 SH035004
6	0.25	6.4	14.7	10.5	42.0	25.4	0.34	FC350-05 SH035005
8	0.31	7.9	17.3	10.5	42.0	31.8	0.35	FC350-06 SH035006
11	0.41	10.4	19.6	8.7	35.0	44.5	0.43	FC350-08 SH035008
12	0.50	12.7	23.9	8.7	35.0	57.2	0.59	FC350-10 SH035010
16	0.63	16.0	27.4	5.2	21.0	69.9	0.68	FC350-12 SH035012
22	0.88	22.4	31.2	2.8	11.2	88.9	0.74	FC350-16 SH035016
29	1.12	28.4	38.1	2.1	8.4	114.3	0.87	FC350-20 SH035020
35	1.38	35.1	44.5	1.7	7.0	139.7	1.02	FC350-24 DH035024