



GH194-液压软管

Hydraulic hose

- 软管结构: 一层钢丝编织增强层, AQP聚酯内层, 蓝色AQP聚酯外层
- 应用: 石油和耐燃液压油、燃料油和润滑油、汽油、水和其他工业液压油。
- 适配接头: 一体式或两件式, 编织类扣压接头
- SAE 100R1AT S型, EN853 1SN
ISO 1436-1 1SN型
- 温度范围: -40°C~+150°C

- Hose structure: one steel wire braided reinforcement layer, AQP polyester inner layer, blue AQP polyester outer layer
- Application: petroleum and fire-resistant hydraulic oils, fuel oil and lubricating oil, gasoline, water and other industrial hydraulic oils.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R1AT S type, EN853 1SN
ISO 1436-1 1SN type
- Temperature range: -40°C~+150°C

							#	型号	产品编码
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m		Type	Product Code
6	1/4	6.4	13.5	22.7	90	100	0.25	GH194-04	SH019404
10	3/8	9.7	17.5	21.0	84	125	0.37	GH194-06	SH019406
12	1/2	12.7	20.6	17.5	70	180	0.45	GH194-08	SH019408
16	5/8	16.0	23.9	14.0	56	205	0.54	GH194-10	SH019410
20	3/4	19.1	27.7	12.4	50	240	0.68	GH194-12	SH019412
25	1	25.4	35.8	9.0	36	300	0.98	GH194-16	SH019416
32	1 1/4	31.8	43.9	6.2	35	420	1.26	GH194-20	SH019420
40	1 1/2	38.1	52.1	5.0	20	500	1.58	GH194-24	SH019424
50	2	50.8	65.5	4.0	16	630	2.04	GH194-32	SH019432



GH195-高温液压管

High temperature hydraulic pipe

- 软管结构: 二层钢丝编织增强层, AQP聚酯内层, 蓝色AQP聚酯外层
- 应用: 石油和耐燃液压油、燃料油和润滑油系统。
- 适配接头: 一体式或两件式, 编织类扣压接头
- SAE 100R2AT S型, EN853 2SN, ISO 1436-1 2SN型
- 温度范围: -40°C~+150°C

- Hose structure: two layers of steel wire braided reinforcement, AQP polyester inner layer, blue AQP polyester outer layer
- Application: petroleum and flame-resistant hydraulic oil, fuel oil and lubricating oil systems.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R2AT S type, EN853 2SN, ISO 1436-1 2SN type
- Temperature range: -40°C~+150°C

							#	型号	产品编码
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m		Type	Product Code
6	1/4	6.4	15.2	40.0	160	102	0.40	GH195-04	SH019504
10	3/8	9.7	19.1	35.0	140	127	0.60	GH195-06	SH019506
12	1/2	12.7	22.1	39.7	119	178	0.68	GH195-08	SH019508
16	5/8	16.0	25.2	22.7	90	203	0.80	GH195-10	SH019510
20	3/4	19.1	29.5	21.0	54	241	1.00	GH195-12	SH019512
25	1	25.4	37.9	17.5	70	305	1.44	GH195-16	SH019516
32	1 1/4	31.8	48.8	15.7	63	419	2.39	GH195-20	SH019520
40	1 1/2	38.1	54.6	12.2	49	508	2.60	GH195-24	SH019524
50	2	50.8	67.8	10.5	42	635	3.38	GH195-32	SH019532