



GH001-空调管

Air conditioning pipe

- 软管结构: 一层合成橡胶衬垫层, 一层稳定的合成编织加强层, 聚酰胺内层, 氯丁基橡胶外层
- 应用: 运输车辆、制冷和空调系统。
- E-Z夹系统或特别连接的铝/钢卷专门用于制冷配件
- SAE J2604-E1
- 温度范围: -35°C~+125°C
- Hose structure: one synthetic rubber liner, one stable synthetic braid reinforcement layer, polyamide inner layer, chlorobutyl rubber outer layer
- Application: transportation vehicles, refrigeration and air conditioning systems.
- E-Z clamp system or specially connected aluminum/steel coils are specially used for refrigeration accessories
- SAE J2604-E1
- Temperature range: -35°C~+125

									
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	负压 kpa	型号 Type	产品编码 Product Code
5	0.19	4.8	11.6	3.5	14	38.1	0.100	94.8	GH001-04 SH000104
8	0.31	7.9	14.7	3.5	14	50.0	0.135	94.8	GH001-06 SH000106
10	0.41	10.3	17.8	3.5	14	63.0	0.177	94.8	GH001-08 SH000108
12	0.50	12.7	19.8	3.5	14	76.2	0.223	94.8	GH001-10 SH000110
16	0.63	15.9	24.9	3.5	14	101.6	0.269	94.8	GH001-12 SH000112
19	0.88	22.4	31.2	3.5	14	127.0	0.430	94.8	GH001-16 SH000116



FESW 铁氟龙管 - 内层光面系列

Teflon Tube - Inner Smooth Series

- 软管结构: 光面DUPONT 62优质PTFE粉末挤压型成内层, SS304不锈钢钢丝编织层外层。
- 温度范围: -73°C~+260°C
- 适配接头: 两件式扣压接头
- Hose structure: smooth DUPONT 62 high-quality PTFE powder unextruded inner layer, SS304 stainless steel wire braided outer layer.
- Temperature range: -73°C~+260°C
- Adapter: two-piece crimping connector

公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
3	1/8	3.4	6.4	33.3	100	38	FESW 2002	SH3002
5	3/16	5.2	8.1	28.7	86	71	FESW 3051	SH3051
6	1/4	6.8	9.4	23.0	69	81	FESW 3067	SH3067
8	5/16	8.5	11.1	21.4	64	127	FESW 3084	SH3084
10	3/8	9.6	12.6	23.0	69	127	FESW 1106	SH3006
11	13/32	10.3	13.2	20.7	62	133	FESW 1007	SH3007
12	1/2	13.5	16.6	16.6	50	178	FESW 3134	SH3134
16	5/8	16.6	19.8	11.0	35	203	FESW 3166	SH3166
20	3/4	19.8	23.0	10.3	31	229	FESW 3198	SH3198
22	7/8	22.1	25.3	9.2	28	229	FESW 1014	SH3014
25	1	26.1	29.3	7.0	21	305	FESW 3261	SH3261