



## EV 45度组合接头 45 degree combined connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径		尺寸			六角		螺纹	重量	型号	产品编码
D1	L1	L2	L3	S1	S2	P1	kg/100	Type	Product Code	
6	9	16	26	14	14	M12x1.5	3.7	EV06L	BF7100606	
8	12	19	27.5	14	17	M14x1.5	4.9	EV08L	BF7100808	
10	12	19	29	19	19	M16x1.5	7.7	EV10L	BF7101010	
12	14	21	29.5	19	22	M18x1.5	8.6	EV12L	BF7101212	
15	17	24	32.5	22	27	M22x1.5	14.4	EV15L	BF7101515	
18	16.5	24	35.5	27	32	M26x1.5	21.0	EV18L	BF7101818	
22	18.5	26	38.5	30	36	M30x2	27.0	EV22L	BF7102222	
28	23	30.5	41.5	36	41	M36x2	38.5	EV28L	BF7102828	
35	26.5	37	51	50	50	M45x2	80.5	EV35L	BF7103535	
42	26	37	56	50	60	M52x2	88.7	EV42L	BF7104242	
6	9	16	27	14	17	M14x1.5	5.0	EV06S	BF7600606	
8	12	19	27.5	19	19	M16x1.5	8.0	EV08S	BF7600808	
10	13.5	21	30	19	22	M18x1.5	9.5	EV10S	BF7601010	
12	16.5	24	31	22	24	M20x1.5	13.7	EV12S	BF7601212	
16	15.5	24	36.5	27	30	M24x1.5	21.7	EV16S	BF7601616	
20	16	26.5	44.5	30	36	M30x2	31.3	EV20S	BF7602020	
25	18.5	30.5	50	36	46	M36x2	52.9	EV25S	BF7602525	
30	23.5	37	55	50	50	M42x2	94.0	EV30S	BF7603030	
38	21	37	63	50	60	M52x2	105.5	EV38S	BF7603838	