



SV 直通隔板式接头 Straight through bulkhead connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢

- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径	尺寸		六角		螺纹	重量	型号	产品编码
D1	L1	L2	S1	S2	P1	kg/100	Type	Product Code
6	34	48	17	17	M12x1.5	4.0	SV06L	BF6110606
8	35	49	19	19	M14x1.5	5.0	SV08L	BF6110808
10	38	52	22	22	M16x1.5	6.5	SV10L	BF6111010
12	39	53	24	24	M18x1.5	7.5	SV12L	BF6111212
15	43	57	27	30	M22x1.5	13.0	SV15L	BF6111515
18	46	61	32	36	M26x1.5	19.5	SV18L	BF6111818
22	51	66	36	41	M30x2	25.5	SV22L	BF6112222
28	54	69	41	50	M36x2	34.0	SV28L	BF6112828
35	55	76	50	60	M45x2	49.4	SV35L	BF6113535
42	55	77	60	65	M52x2	71.6	SV42L	BF6114242
6	41	55	19	19	M14x1.5	6.3	SV06S	BF6210606
8	42	56	22	22	M16x1.5	9.0	SV08S	BF6210808
10	44	59	24	24	M18x1.5	11.3	SV10S	BF6211010
12	45	60	27	27	M20x1.5	14.0	SV12S	BF6211212
14	49	65	30	30	M22x1.5	18.0	SV14S	BF6211414
16	49	65	32	32	M24x1.5	17.5	SV16S	BF6211616
20	51	72	41	41	M30x2	33.2	SV20S	BF6212020
25	55	79	46	46	M36x2	49.5	SV25S	BF6212525
30	59	86	50	50	M42x2	66.4	SV30S	BF6213030
38	59	91	65	65	M52x2	105.9	SV38S	BF6213838