



ET 三通组合接头 Three-way combination connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径		尺寸			六角		螺纹	重量	型号	产品编码
D1	L1	L2	L3	S1	S2	P1	kg/100	Type	Product Code	
6	14	21	26	12	17	M12x1.5	3.2	ET06L	BF3110606	
8	14	21	27.5	12	17	M14x1.5	6.5	ET08L	BF3110808	
10	15	22	29	14	19	M16x1.5	9.5	ET10L	BF3111010	
12	17	24	29.5	17	22	M18x1.5	12.5	ET12L	BF3111212	
15	21	28	32.5	19	27	M22x1.5	14.0	ET15L	BF3111515	
18	23.5	31	35.5	24	32	M26x1.5	21.5	ET18L	BF3111818	
22	27.5	35	38.5	27	36	M30x2	28.0	ET22L	BF3112222	
28	30.5	38	41.5	36	46	M36x2	49.0	ET28L	BF3112828	
35	34.5	45	51	41	50	M45x2	60.9	ET35L	BF3113535	
42	40	51	56	50	60	M52x2	89.2	ET42L	BF3114242	
6	16	23	27	12	17	M14x1.5	8.0	ET06S	BF3610606	
8	17	24	27.5	14	19	M16x1.5	10.5	ET08S	BF3610808	
10	17.5	25	30	17	22	M18x1.5	14.0	ET10S	BF3611010	
12	21.5	29	31	17	24	M20x1.5	19.0	ET12S	BF3611212	
14	22	30	35	19	27	M22x1.5	16.9	ET14S	BF3611414	
16	24.5	33	36.5	24	30	M24x1.5	23.0	ET16S	BF3611616	
20	26.5	37	44.5	27	36	M30x2	35.0	ET20S	BF3612020	
25	30	42	50	36	46	M36x2	63.5	ET25S	BF3612525	
30	35.5	49	55	41	50	M42x2	87.0	ET30S	BF3613030	
38	41	57	63	50	60	M52x2	131.0	ET38S	BF3613838	