



**WEE-ROG**  
**弯通可调向接头**  
 Bent-through adjustable  
 connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸				六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code	
6	14	21	19	7	14	14	M12x1.5	G1/8A	6.6	WEE06LROG	BF2040602	
8	16	23	23	9	14	19	M14x1.5	G1/4A	6.6	WEE08LROG	BF2040804	
10	17	24	25	9	19	19	M16x1.5	G1/4A	11.9	WEE10LROG	BF2041004	
12	19	26	28	9	19	22	M18x1.5	G3/8A	13.8	WEE12LROG	BF2041206	
15	21	28	30	13	22	27	M22x1.5	G1/2A	28.3	WEE15LROG	BF2041508	
18	24	31	36	13	27	27	M26x1.5	G1/2A	34.4	WEE18LROG	BF2041808	
22	28	35	36	13	30	36	M30x2	G3/4A	44.9	WEE22LROG	BF2042212	
28	31	38	44	15	36	41	M36x2	G1A	65.7	WEE28LROG	BF2043816	
35	38	48	50	15	50	50	M45x2	G1 1/4A	111.3	WEE35LROG	BF2043520	
42	38	49	52	15	50	55	M52x2	G1 1/2A	119.7	WEE42LROG	BF2044224	
6	15	22	23	9	14	19	M14x1.5	G1/4A	6.9	WEE06SROG	BF2540604	
8	17	24	27	9	19	19	M16x1.5	G1/4A	12.0	WEE08SROG	BF2540804	
10	18	25	29	9	19	22	M18x1.5	G3/8A	13.8	WEE10SROG	BF2541006	
12	22	29	29	9	22	22	M20x1.5	G3/8A	20.6	WEE12SROG	BF2541206	
16	25	33	36	13	27	27	M24x1.5	G1/2A	34.6	WEE16SROG	BF2541608	
20	28	38	39	12	30	36	M30x2	G3/4A	46.8	WEE20SROG	BF2542012	
25	30	42	44	14	36	41	M36x2	G1A	77.2	WEE25SROG	BF2542516	
30	36	49	49	15	50	50	M42x2	G1 1/4A	106.9	WEE30SROG	BF2543020	
38	34	50	55	15	50	55	M52x2	G1 1/2A	131.1	WEE38SROG	BF2543824	