



WH-M-KDS 高压铰接式接头 High pressure articulated connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢

- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸				六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code	
6	12	19	8	10.5	17	17	M12x1.5	M10x1	5.4	WH06LMKDS	BF5110610	
8	14.5	21.5	12	14	22	19	M14x1.5	M12x1.5	9.7	WH08LMKDS	BF5110812	
10	15.5	22.5	12	14	22	19	M16x1.5	M14x1.5	10.4	WH10LMKDS	BF5111014	
12	18	25	12	16.5	27	24	M18x1.5	M16x1.5	18.0	WH12LMKDS	BF5111216	
15	21.5	27.5	12	18.5	30	30	M22x1.5	M18x1.5	24.4	WH15LMKDS	BF5111518	
18	21	28.5	14	21.5	32	30	M26x1.5	M22x1.5	32.7	WH18LMKDS	BF5111822	
22	27.5	35	16	24	41	36	M30x2	M26x1.5	57.3	WH22LMKDS	BF5112226	
28	32	39.5	18	30.5	50	46	M36x2	M33x2	101.7	WH28LMKDS	BF5112833	
35	36	46.5	20	35.5	60	55	M45x2	M42x2	151.2	WH35LMKDS	BF5113542	
42	40.5	51.5	22	40.5	70	60	M52x2	M48x2	221.7	WH42LMKDS	BF5114248	
6	16.5	23.5	12	14	22	19	M14x1.5	M12x1.5	10.4	WH06SMKDS	BF5210612	
8	16.5	23.5	12	14	22	19	M16x1.5	M14x1.5	11.0	WH08SMKDS	BF5210814	
10	18.5	26	12	16.5	27	24	M18x1.5	M16x1.5	18.6	WH10SMKDS	BF5211016	
12	20	27.5	12	18.5	27	27	M20x1.5	M18x1.5	24.6	WH12SMKDS	BF5211218	
14	22.5	30.5	14	20	32	30	M22x1.5	M20x1.5	32.2	WH14SMKDS	BF5211420	
16	22	30.5	14	21.5	32	30	M24x1.5	M22x1.5	32.7	WH16SMKDS	BF5211622	
20	26.5	37	16	24	41	36	M30x2	M27x2	59.8	WH20SMKDS	BF5212027	
25	31.5	43.5	18	30.5	50	46	M36x2	M33x2	105.5	WH25SMKDS	BF5212533	
30	37	50.5	20	35.5	60	55	M42x2	M42x2	157.2	WH30SMKDS	BF5213042	
38	41.5	57.5	22	40.5	70	60	M52x2	M48x2	231.7	WH38SMKDS	BF5213848	