


**VEE-ROG**  
**可调向45度接头**  
 Adjustable 45-degree  
 connector



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸				六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code	
6	9	24	21	7	14	14	M12x1.5	G1/8A	5.0	VEE06LROG	BF7040602	
8	12	27	20	9	14	19	M14x1.5	G1/4A	5.5	VEE08LROG	BF7040804	
10	12	27	25	9	19	19	M16x1.5	G1/4A	10.5	VEE10LROG	BF7041004	
12	14	28	28	9	19	22	M18x1.5	G3/8A	14.7	VEE12LROG	BF7041206	
15	17	32	26	13	22	27	M22x1.5	G1/2A	20.2	VEE15LROG	BF7041508	
18	17	33	32	13	27	27	M26x1.5	G1/2A	26.1	VEE18LROG	BF7041808	
22	19	35	37	13	30	36	M30x2	G3/4A	38.8	VEE22LROG	BF7042212	
28	23	40	37	15	36	41	M36x2	G1A	50.0	VEE28LROG	BF7043816	
35	27	48	39	15	50	50	M45x2	G1 1/4A	71.1	VEE35LROG	BF7043520	
42	26	49	39	15	50	55	M52x2	G1 1/2A	79.5	VEE42LROG	BF7044224	
6	9	24	19	9	14	19	M14x1.5	G1/4A	5.8	VEE06SROG	BF7540604	
8	12	27	23	9	19	19	M16x1.5	G1/4A	10.6	VEE08SROG	BF7540804	
10	13	29	25	9	19	22	M18x1.5	G3/8A	12.7	VEE10SROG	BF7541006	
12	17	33	25	9	19	22	M20x1.5	G3/8A	15.6	VEE12SROG	BF7541206	
16	16	34	31	13	19	27	M24x1.5	G1/2A	22.6	VEE16SROG	BF7541608	
20	16	38	34	12	27	36	M30x2	G3/4A	30.5	VEE20SROG	BF7542012	
25	19	43	37	14	36	41	M36x2	G1A	61.5	VEE25SROG	BF7542516	
30	24	50	38	15	50	50	M42x2	G1 1/4A	79.9	VEE30SROG	BF7543020	
38	21	52	38	15	50	55	M52x2	G1 1/2A	90.9	VEE38SROG	BF7543824	