



GE-RK 外螺纹管接头 Male thread pipe connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢

- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸			六角	螺纹		重量	型号	产品编码
D1	L1	L2	L3	S1	P1	P2	kg/100	Type	Product Code	
6	20	27	12	14	M12x1.5	R1/4keg	2.0	GE06LR1/4K	BF1050604	
8	20	27	12	14	M14x1.5	R1/4keg	2.0	GE08LRK	BF1050804	
8	20	27	12	17	M14x1.5	R3/8keg	3.0	GE08LR3/8K	BF1050806	
10	21	28	12	17	M16x1.5	R1/4keg	2.4	GE10LRK	BF1051004	
10	21	28	12	17	M16x1.5	R3/8keg	2.9	GE10LR3/8K	BF1051006	
12	22	29	12	19	M18x1.5	R1/4keg	3.0	GE12LR1/4K	BF1051204	
12	22	29	12	19	M18x1.5	R3/8keg	3.4	GE12LRK	BF1051206	
12	24	31	14	22	M18x1.5	R1/2keg	4.9	GE12LR1/2K	BF1051208	
15	25	32	14	24	M22x1.5	R1/2keg	5.4	GE15LRK	BF1051508	