



## WH-R-KDS 高压铰接式接头 High pressure articulated connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸			六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code
6	12	19	8	10.5	17	17	M12x1.5	G1/8A	5.3	WH06LRKDS	BF5120602
8	14.5	21.5	12	14	22	19	M14x1.5	G1/4A	10.1	WH08LRKDS	BF5120804
10	15.5	22.5	12	14	22	19	M16x1.5	G1/4A	10.2	WH10LRKDS	BF5121004
12	18	25	12	16.5	27	24	M18x1.5	G3/8A	18.1	WH12LRKDS	BF5121206
15	21.5	28.5	14	21.5	32	30	M22x1.5	G1/2A	31.2	WH15LRKDS	BF5121508
18	21	28.5	14	21.5	32	30	M26x1.5	G1/2A	31.9	WH18LRKDS	BF5121808
22	27.5	35	16	24	41	36	M30x2	G3/4A	57.8	WH22LRKDS	BF5122212
28	32	39.5	18	30.5	50	46	M36x2	G1A	103.5	WH28LRKDS	BF5122816
35	36	46.5	20	35.5	60	55	M45x2	G1 1/4A	149.9	WH35LRKDS	BF5123520
42	40.5	51.5	22	40.5	70	60	M52x2	G1 1/2A	219.6	WH42LRKDS	BF5124224
6	16.5	23.5	12	14	22	19	M14x1.5	G1/4A	10.7	WH06SRKDS	BF5220604
8	16.5	23.5	12	14	22	19	M16x1.5	G1/4A	10.7	WH08SRKDS	BF5220804
10	18.5	26	12	16.5	27	24	M18x1.5	G3/8A	18.8	WH10SRKDS	BF5221006
12	18.5	26	12	16.5	27	24	M20x1.5	G3/8A	19.0	WH12SRKDS	BF5221206
14	22.5	30.5	15	21.5	32	30	M22x1.5	G1/2A	32.0	WH14SRKDS	BF5221408
16	22	30.5	14	21.5	32	30	M24x1.5	G1/2A	32.4	WH16SRKDS	BF5221608
20	26.5	37	16	24	41	36	M30x2	G3/4A	58.8	WH20SRKDS	BF5222012
25	31.5	43.5	18	30.5	50	46	M36x2	G1A	107.3	WH25SRKDS	BF5222516
30	37	50.5	20	35.5	60	55	M42x2	G1 1/4A	155.9	WH30SRKDS	BF5223020
38	41.5	57.5	22	40.5	70	60	M52x2	G1 1/4A	229.6	WH38SRKDS	BF5223824