


**TH-R-KDS**  
**高压绞接式三通接头**  
 High voltage twisted tee  
 connector



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸			六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code
6	12	19	8	10.5	17	17	M12x1.5	M10x1	5.8	TH06LRKDS	BF5140602
8	14.5	21.5	12	14	22	19	M14x1.5	M12x1.5	10.8	TH08LRKDS	BF5140804
10	15.5	22.5	12	14	22	19	M16x1.5	M14x1.5	11.0	TH10LRKDS	BF5141004
12	18	25	12	16.5	27	24	M18x1.5	M16x1.5	19.3	TH12LRKDS	BF5141206
15	21.5	28.5	14	21.5	32	30	M22x1.5	M18x1.5	32.1	TH15LRKDS	BF5141508
18	21	28.5	14	21.5	32	30	M26x1.5	M22x1.5	32.9	TH18LRKDS	BF5141808
22	27.5	35	16	24	41	36	M30x2	M26x1.5	58.5	TH22LRKDS	BF5142212
28	32	39.5	18	30.5	50	46	M36x2	M33x2	109.0	TH28LRKDS	BF5142816
35	36	46.5	20	35.5	60	55	M45x2	M42x2	176.5	TH35LRKDS	BF5143520
42	40.5	51.5	22	40.5	70	60	M52x2	M48x2	254.5	TH42LRKDS	BF5144224
6	16.5	23.5	12	14	22	19	M14x1.5	M12x1.5	11.6	TH06SRKDS	BF5240604
8	16.5	23.5	12	14	22	19	M16x1.5	M14x1.5	12.1	TH08SRKDS	BF5240804
10	18.5	26	12	16.5	27	24	M18x1.5	M16x1.5	20.1	TH10SRKDS	BF5241006
12	18.5	26	12	16.5	27	24	M20x1.5	M18x1.5	20.7	TH12SRKDS	BF5241206
14	22.5	30.5	15	21.5	32	30	M22x1.5	M20x1.5	33.8	TH14SRKDS	BF5241408
16	22	30.5	14	21.5	32	30	M24x1.5	M22x1.5	35.0	TH16SRKDS	BF5241608
20	26.5	37	16	24	41	36	M30x2	M27x2	52.0	TH20SRKDS	BF5242012
25	31.5	43.5	18	30.5	50	46	M36x2	M33x2	112.4	TH25SRKDS	BF5242516
30	37	50.5	20	35.5	60	55	M42x2	M42x2	183.0	TH30SRKDS	BF5243020
38	41.5	57.5	22	40.5	70	60	M52x2	M48x2	272.1	TH38SRKDS	BF5243824