


TH-M-KDS

高压绞接式三通接头

High voltage twisted tee connector



■ 符合ISO8434-1, 24°卡套连接作用

■ 常规供货碳钢/表面镀锌, 不锈钢

■ Comply with ISO8434-1, 24° ferrule connection

■ Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸				六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code	
6	12	19	8	10.5	17	17	M12x1.5	M10x1	5.9	TH06LMKDS	BF5130610	
8	14.5	21.5	12	14	22	19	M14x1.5	M12x1.5	10.4	TH08LMKDS	BF5130812	
10	15.5	22.5	12	14	22	19	M16x1.5	M14x1.5	11.2	TH10LMKDS	BF5131014	
12	18	25	12	16.5	27	24	M18x1.5	M16x1.5	19.2	TH12LMKDS	BF5131216	
15	21.5	27.5	12	18.5	30	27	M22x1.5	M18x1.5	25.8	TH15LMKDS	BF5131518	
18	21	28.5	14	21.5	32	30	M26x1.5	M22x1.5	33.7	TH18LMKDS	BF5131822	
22	27.5	35	16	24	41	36	M30x2	M26x1.5	58.9	TH22LMKDS	BF5132226	
28	32	39.5	18	30.5	50	46	M36x2	M33x2	107.2	TH28LMKDS	BF5132833	
35	36	46.5	20	35.5	60	55	M45x2	M42x2	177.8	TH35LMKDS	BF5133542	
42	40.5	51.5	22	40.5	70	60	M52x2	M48x2	256.6	TH42LMKDS	BF5134248	
6	16.5	23.5	12	14	22	19	M14x1.5	M12x1.5	11.2	TH06SMKDS	BF5230612	
8	16.5	23.5	12	14	22	19	M16x1.5	M14x1.5	12.3	TH08SMKDS	BF5230814	
10	18.5	26	12	16.5	27	24	M18x1.5	M16x1.5	20.0	TH10SMKDS	BF5231016	
12	20	27.5	12	18.5	27	27	M20x1.5	M18x1.5	26.1	TH12SMKDS	BF5231218	
14	22.5	30.5	14	20	32	30	M22x1.5	M20x1.5	33.4	TH14SMKDS	BF5231420	
16	22	30.5	14	21.5	32	30	M24x1.5	M22x1.5	35.1	TH16SMKDS	BF5231622	
20	26.5	37	16	24	41	36	M30x2	M27x2	62.9	TH20SMKDS	BF5232027	
25	31.5	43.5	18	30.5	50	46	M36x2	M33x2	110.6	TH25SMKDS	BF5232533	
30	37	50.5	20	35.5	60	55	M42x2	M42x2	184.3	TH30SMKDS	BF5233042	
38	41.5	57.5	22	40.5	70	60	M52x2	M48x2	274.4	TH38SMKDS	BF5233848	