



## DGWES-R-ED

### 旋转式铰接式接头

#### Swivel articulated connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径	尺寸				六角		螺纹		重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	P1	P2	kg/100	Type	Product Code
6	16.5	23.5	21.5	8	27	17	M12x1.5	G1/8A		DGWES06LRED	BF5150602
6	16.5	23.5	22.5	12	27	19	M12x1.5	G1/4A		DGWES06LR1/4ED	BF5150604
8	18	25	25	12	30	22	M14x1.5	G1/4A		DGWES08LRED	BF5150804
10	19	26	25	12	30	22	M16x1.5	G1/4A		DGWES10LRED	BF5151004
10	20	27	27	12	32	24	M16x1.5	G3/8A		DGWES10LR3/8ED	BF5151006
12	20	27	27	12	32	24	M18x1.5	G3/8A		DGWES12LRED	BF5151206
12	22	29	30	14	36	27	M18x1.5	G1/2A		DGWES12LR1/2ED	BF5151208
15	25	32	33	14	40	32	M22x1.5	G1/2A		DGWES15LRED	BF5151508
18	24.5	32	33	14	40	32	M26x1.5	G1/2A		DGWES18LRED	BF5151808
22	29	36.5	35.5	16	45	36	M30x2	G3/4A		DGWES22LRED	BF5152212
28	38	45.5	41.5	18	55	41	M36x2	G1A		DGWES28LRED	BF5152816
35	38	48.5	51.5	20	65	50	M45x2	G1 1/4A		DGWES35LRED	BF5153520
42	42.5	53.5	56.5	22	75	55	M52x2	G1 1/2A		DGWES42LRED	BF5154224
6	18.5	25.5	22.5	12	27	19	M14x1.5	G1/4		DGWES06SRED	BF5250604
8	18.5	25.5	22.5	12	27	19	M16x1.5	G1/4		DGWES08SRED	BF5250804
10	19.5	27	25	12	30	22	M18x1.5	G3/8A		DGWES10SRED	BF5251006
12	20.5	28	27	12	32	24	M20x1.5	G3/8A		DGWES12SRED	BF5251206
14	24	32	30	14	36	27	M22x1.5	G1/2A		DGWES14SRED	BF5251408
16	25.5	34	33	14	40	32	M24x1.5	G1/2A		DGWES16SRED	BF5251608
20	28	38.5	35.5	16	45	36	M30x2	G3/4A		DGWES20SRED	BF5252012
25	33.5	45.5	41.5	18	55	41	M36x2	G1A		DGWES25SRED	BF5252516
30	39	52.5	51.5	20	65	50	M42x2	G1 1/4A		DGWES30SRED	BF5253020
38	43.5	59.5	56.5	22	75	55	M52x2	G1 1/2A		DGWES38SRED	BF5253824