



## BFG

### 齿轮泵直通液压

#### Gear pump direct hydraulic

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径		尺寸				螺纹	重量	适用螺栓	O型圈	型号	产品编码
D1	D2	L1	L2	L3	L4	P1	kg/100	公制/Metric	O-Ring	Type	Product Code
10L	6.4	23	30	39	35	M16x1.5	15.0	M6x22	20x2.5	BFG10L/LK35	BF8171035
12L	6.4	23	30	39	35	M18x1.5	16.0	M6x22	20x2.5	BFG12L/LK35	BF8171235
15L	6.4	23	30	39	35	M22x1.5	19.0	M6x22	20x2.5	BFG15L/LK35	BF8171535
15L	6.4	28	35	42	40	M22x1.5	17.0	M6x22	26x2.5	BFG15L/LK40	BF8171540
18L	6.4	27.5	35	42	40	M26x1.5	22.0	M6x22	26x2.5	BFG18L/LK40	BF8171840
22L	6.4	27.5	35	42	40	M30x2	24.0	M6x22	26x2.5	BFG22L/LK40	BF8172240
28L	6.4	27.5	35	42	40	M36x2	28.0	M6x22	26x2.5	BFG28L/LK40	BF8172840
16S	6.4	21.5	30	39	35	M24x1.5	21.0	M6x22	20x2.5	BFG16S/LK35	BF8271635
20S	8.4	39.5	50	57	55	M30x2	35.0	M8x25	32x2.5	BFG20S/LK35	BF8272035