


20SF AW 气动快换-公头

Pneumatic quick change-male



- 口径 $2,7=6\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度：
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $2,7=6\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)


| 尺寸 | | 六角 | 螺纹 | 型号 | 产品编码 |
|----|----|----|------|--------------|--------------|
| L1 | L2 | S1 | P1 | Type | Product Code |
| 5 | 18 | 7 | M5 | 20SFAW05 MXX | QC93000007 |
| | | | | 20SFAW05 MXN | QC93000008 |
| 7 | 20 | 11 | G1/8 | 20SFAW10 MXX | QC93000009 |
| | | | | 20SFAW10 MXN | QC93000010 |

注：MXX为标准，MXN为镀镍

Note: MXX is standard, MXN is nickel-plated

20SB AW 气动快换-公头

Pneumatic quick change-male



- 口径 $2,7=5\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度：
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $2,7=5\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

| 尺寸 | | 六角 | 螺纹 | 型号 | 产品编码 |
|----|----|----|------|---------------|--------------|
| L1 | L2 | S1 | P1 | Type | Product Code |
| 5 | 28 | 9 | M5 | 20SB AW05 MPX | QC93000011 |
| | | | | 20SB AW05 MPN | QC93000012 |
| 7 | 30 | 11 | G1/8 | 20SB AW10 MPX | QC93000013 |
| | | | | 20SB AW10 MPN | QC93000014 |

注：MPX为标准，MPN为镀镍

Note: MPX is standard, MPN is nickel-plated