


20KB KO

气动快换-母头

Pneumatic quick change-female



- 口径 $2,7=5\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $2,7=5\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

尺寸		六角 S1	螺纹 P1	型号 Type	产品编码 Product Code
L1	L2				
3x4mm			M7x0.5	20KB KO04 MPX	QC96000009
				20KB KO04 MPN	QC96000010
3x5mm			M7x0.5	20KB KO05 MPX	QC96000011
				20KB KO05 MPN	QC96000012
4x6mm			M8x0.5	20KB KO06 MPX	QC96000013
				20KB KO06 MPN	QC96000014


注: MPX为标准, MPN为镀镍

Note: MPX is standard, MPN is nickel plated

21KB AW/AD

气动快换-母头

Pneumatic quick change-female



- 口径 $5=20\text{mm}^2$
- 常用于小型气动、医疗、化学和制药行业
- 工作压力 $PB=35\text{bar}$
- 适用温度:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

- Orifice $5=20\text{mm}^2$
- Commonly used in small pneumatic, medical, chemical and pharmaceutical industries
- Working pressure $PB=35\text{bar}$
- Applicable temperature:
 - 20°C~+100°C (NBR)
 - 40°C~+120°C (EPDM)
 - 15°C~+200°C (FKM)

尺寸		六角 S1	螺纹 P1	型号 Type	产品编码 Product Code
L1	L2				
7	36	14	G1/8	21KB AW10 MPX	QC96000015
				21KB AW10 MPN	QC96000016
9	38	17	G1/4	21KB AW13 MPX	QC96000017
				21KB AW13 MPN	QC96000018
9	38	19	G3/8	21KB AW17 MPX	QC96000019
				21KB AW17 MPN	QC96000020
8	37	14	M10x1	21KB AD10 MPX	QC96000021
				21KB AD10 MPN	QC96000022
10	39	17	M12x1.5	21KB AD12 MPX	QC96000023
				21KB AD12 MPN	QC96000024
10	39	17	M14x1.5	21KB AD14 MPX	QC96000025
				21KB AD14 MPN	QC96000026

注: MPX为标准, MPN为镀镍

Note: MPX is standard, MPN is nickel plated