


DG 107

直通隔板式滚珠轴承旋转接头

Straight through bulkhead ball bearing swivel connector




- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径	尺寸				六角			螺纹	重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	S3	P1	kg/100	Type	Product Code
6	72	16	42	5	22	17	17	M14x1.5	13.4	DG107/06S	RU1750606
8	72	16	42	5	22	17	19	M16x1.5	14.3	DG107/08S	RU1750808
12	83	15.5	52.5	5	30	24	24	M20x1.5	29.1	DG107/12S	RU1751212
16	86	17.5	51.5	5	30	27	30	M24x1.5	32.8	DG107/16S	RU1751616
20	115	28.5	65.5	15	41	36	36	M30x2	71.0	DG107/20S	RU1752020
25	120	30	66	15	41	41	46	M36x2	84.7	DG107/25S	RU1752525
30	133	30.5	75.5	15	60	46	50	M42x2	153.3	DG107/30S	RU1753030
38	139	31	76	15	60	55	60	M52x2	193.0	DG107/38S	RU1753838

DG 108

直角隔板式滚珠轴承旋转接头

Right Angle Bulkhead Ball Bearing Rotary connector



- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- Comply with ISO8434-1, 24° ferrule connection
- Generally supplied carbon steel/galvanized surface, stainless steel

钢管外径	尺寸				六角			螺纹	重量	型号	产品编码
D1	L1	L2	L3	L4	S1	S2	S3	P1	kg/100	Type	Product Code
6	16	62.5	16	23	22	17	19	M14x1.5	15.4	DG108/06S	RU1850606
8	16	62.5	17	23	22	17	22	M16x1.5	16.6	DG108/08S	RU1850808
12	15.5	74	21.5	29	30	22	27	M20x1.5	33.3	DG108/12S	RU1851212
16	17.5	75	24.5	33	30	22	32	M24x1.5	35.4	DG108/16S	RU1851616
20	28.5	106	26.5	37	41	36	41	M30x2	90.4	DG108/20S	RU1852020
25	30	107	30	42	41	36	46	M36x2	99.9	DG108/25S	RU1852525
30	30.5	126.5	35.5	49	60	50	50	M42x2	193.5	DG108/30S	RU1853030
38	31	127.5	41	57	60	50	65	M52x2	235.1	DG108/38S	RU1853838