



PBV1 快换接头 Quick-change connector

- 符合ISO7241-2
- 常规供货碳钢/表面镀锌, 黄色钢
- 工作温度: - 25°C ~+ 125°C
- 标准密封: 丁腈橡胶
- Complies with ISO7241-2
- Generally available Carbon steel/galvanized surface, yellow steel
- Working temperature: - 25°C ~+ 125°C
- Standard seal: Nitrile rubber

公称尺寸 (ISO)	尺寸			六角		螺纹		型号 (母头F)	产品编码	型号 (公头M)	产品编码	
D1	L1	L2	L3	L4	S1	S2	P1	Type	Product Code	Type	Product Code	
6.3	60	38	76	28	19	19	G1/4A	PBV1.0606.002	QC21150404	PBV1.0606.003	QC21100404	
								1/4NPT	PBV1.0606.012	QC21170404	PBV1.0606.013	QC21120404
10	67.5	43	86	35	22	22	G3/8A	PBV1.1010.002	QC21250606	PBV1.1010.003	QC21200606	
								3/8NPT	PBV1.1010.012	QC21270606	PBV1.1010.013	QC21220606
								3/4UNF			PBV1.1019.033	QC21231212
12.5	76	48.5	97	44	27	27	G1/2A	PBV1.1313.002	QC21350808	PBV1.1313.003	QC21300808	
								1/2NPT	PBV1.1313.012	QC21370808	PBV1.1313.013	QC21320808
20	91.5	57	114	52	34	34	G3/4A	PBV1.2019.002	QC21451212	PBV1.2019.003	QC21401212	
								3/4NPT	PBV1.2019.012	QC21471212	PBV1.2019.013	QC21421212
25	106	65.5	131	60	41	41	G1A	PBV1.2525.002	QC21551616	PBV1.2525.003	QC21501616	
								1NPT	PBV1.2525.012	QC21571616	PBV1.2525.013	QC21521616
40	126	126	198	75	65	65	G1 1/4A	PBV1.3931.002	QC21752020	PBV1.3931.003	QC21702020	
								1 1/4NPT	PBV1.3931.012	QC21772020	PBV1.3931.013	QC21722020
								G1 1/2A	PBV1.3939.002	QC21752424	PBV1.3939.003	QC21702424
								1 1/2NPT	PBV1.3939.012	QC21772424	PBV1.3939.013	QC21722424
50	142	142	222	105	90	90	G2A	PBV1.5051.002	QC21853232	PBV1.5051.003	QC21803232	
								2NPT	PBV1.5051.012	QC21873232	PBV1.5051.013	QC21823232

公称尺寸 ISO	公称通径 DN(mm)	最大工作压力 Mpa	爆破压力 Mpa	额定流量 L/m
6.3	6.5	25	110	12
10	9	25	143	23
12.5	10.5	25	110	45
20	15.6	25	100	106
25	17.3	20	101	189
40	36	6.3	25	379
50	50	5	20	757