



## VKA3 测压接头 Pressure test connector

- 符合ISO8434-1, 24°卡套连接作用
- 常规供货碳钢/表面镀锌, 不锈钢
- 可提供氟橡胶密封圈
- Complies with ISO8434-1, 24° ferrule connection
- Commonly available carbon steel/galvanized surface, stainless steel
- Fluororubber sealing ring available

钢管外径 D1	尺寸 L1	六角 S1 S2		螺纹 P1	重量 kg/100	图 No	型号 Type	产品编码 Product Code
6	55	14	17	M12x1.5	8.2	1	VKA3/06L	TI01001606
8	51	17	17	M14x1.5	8.2	1	VKA3/08L	TI01001608
10	53	19	17	M16x1.5	9.3	1	VKA3/10L	TI01001610
12	53	22	17	M18x1.5	10.7	1	VKA3/12L	TI01001612
15	59	27	17	M22x1.5	13.3	2	VKA3/15L	TI01001615
18	59	32	17	M26x1.5	16.3	2	VKA3/18L	TI01001618
22	60	36	17	M30x2	20.5	2	VKA3/22L	TI01001622
28	64	41	17	M36x2	26.9	2	VKA3/28L	TI01001628
35	71	50	17	M45x2	41.1	2	VKA3/35L	TI01001635
42	72	60	17	M52x2	59.2	2	VKA3/42L	TI01001642
6	50	17	17	M14x1.5	8.1	1	VKA3/06S	TI01051606
8	52	19	17	M16x1.5	8.8	1	VKA3/08S	TI01051608
10	53	22	17	M18x1.5	9.9	1	VKA3/10S	TI01051610
12	54	24	19	M20x1.5	12.1	1	VKA3/12S	TI01051612
14	59	27	17	M22x1.5	13.6	2	VKA3/14S	TI01051614
16	58	30	17	M24x1.5	15.6	2	VKA3/16S	TI01051616
20	65	36	17	M30x2	22.3	2	VKA3/20S	TI01051620
25	68	46	17	M36x2	36.7	2	VKA3/25S	TI01051625
30	74	50	17	M42x2	44.4	2	VKA3/30S	TI01051630
38	81	60	17	M52x2	65.5	2	VKA3/38S	TI01051638