


PR190 压力传感器 Pressure Sensors

Pin设置	4~20mA (双线)	0~10V (三线)
白	free	signal+
黑	-Ub/signal-	-Ub/signal-/GND
绿	free	free
红	+Ub/signal+	+Ub



- 工作原理: 压阻效应
- 压力类型: 相对压力
- 输出信号: 4~20mA/0~10VDC
- 电气连接: 开放式电缆头, 4线, 长度1.5m
- 机械连接: G1/4A, ISO 228
- 密封材料: DIN3689标准密封, 氟橡胶
- 防护等级: IP68K
- 外壳材料: 不腐蚀的高强度钢
- 膜材料: 不腐蚀的高强度钢
- 拧紧力矩: 40Nm (±5Nm)
- 净重: ~120g

- Working principle: Piezoresistive effect
- Pressure type: relative pressure
- Output signal: 4~20mA/0~10VDC
- Electrical connection: open cable head, 4 wires, length 1.5m
- Mechanical connection: G1/4A, ISO 228
- Seal material: DIN3689 standard seal, fluororubber
- Protection grade: IP68K
- Casing material: non-corrosive high-strength steel
- Membrane material: non-corrosive high-strength steel
- Tightening torque: 40Nm (±5Nm)
- Net weight: ~120g

量程		型号	产品编码	型号	产品编码
bar	Mpa	4~20mA	Product Code	0~10V	Product Code
-1~6	-0.1~0.6	PR190-32-D6.37S	TI45100006	PR190-32-D6.39S	TI45200006
0~10	0~1	PR190-26-D6.37S	TI45100010	PR190-26-D6.39S	TI45200010
0~25	0~2.5	PR190-40-D6.37S	TI45100025	PR190-40-D6.39S	TI45200025
0~60	0~6	PR190-21-D6.37S	TI45100060	PR190-21-D6.39S	TI45200060
0~100	0~10	PR190-16-D6.37S	TI45100100	PR190-16-D6.39S	TI45200100
0~250	0~25	PR190-17-D6.37S	TI45100250	PR190-17-D6.39S	TI45200250
0~400	0~40	PR190-15-D6.37S	TI45100400	PR190-15-D6.39S	TI45200400
0~600	0~60	PR190-18-D6.37S	TI45100600	PR190-18-D6.39S	TI45200600
0~1000	0~100	PR190-29-D6.37S	TI45101000	PR190-29-D6.39S	TI45201000

注: 需要了解更多的数据和产品, 请联系我们

Note: For more information and products, please contact us