


PR130 压力传感器 Pressure Sensors



Pin设置	4~20mA (双线)	0~10V (三线)
	pin 1= -Ub/signal-	pin 1= +Ub
	pin 2= free	pin 2= free
	pin 3= -Ub/signal-	pin 3= -Ub/signal-/GND
	pin 4= free	pin 4= signal+

- 工作原理: 压阻效应
- 压力类型: 相对压力
- 输出信号: 4~20mA/0~10VDC
- 电气连接: 4针插头, M12×1
- 机械连接: G1/4A, ISO 228
- 密封材料: DIN3689标准密封, 氟橡胶
- 防护等级: IP67
- 外壳材料: 不腐蚀的高强度钢
- 膜材料: 不腐蚀的高强度钢
- 拧紧力矩: 40Nm (±5Nm)
- 净重: ~85g

- Working principle: Piezoresistive effect
- Pressure type: relative pressure
- Output signal: 4~20mA/0~10VDC
- Electrical connection: 4-pin plug, M12×1
- Mechanical connection: G1/4A, ISO 228
- Sealing material: DIN3689 standard seal, fluororubber
- Protection grade: IP67
- Casing material: non-corrosive high-strength steel
- Membrane material: non-corrosive high-strength steel
- Tightening torque: 40Nm (±5Nm)
- Net weight: ~85g

量程		型号	产品编码	型号	产品编码
bar	Mpa	4~20mA	Product Code	0~10V	Product Code
-1~6	-0.1~0.6	PR130-32-I5.37S	TI42100006	PR130-32-I5.39S	TI42200006
0~10	0~1	PR130-26-I5.37S	TI42100010	PR130-26-I5.39S	TI42200010
0~25	0~2.5	PR130-40-I5.37S	TI42100025	PR130-40-I5.39S	TI42200025
0~60	0~6	PR130-21-I5.37S	TI42100060	PR130-21-I5.39S	TI42200060
0~100	0~10	PR130-16-I5.37S	TI42100100	PR130-16-I5.39S	TI42200100
0~250	0~25	PR130-17-I5.37S	TI42100250	PR130-17-I5.39S	TI42200250
0~400	0~40	PR130-15-I5.37S	TI42100400	PR130-15-I5.39S	TI42200400
0~600	0~60	PR130-18-I5.37S	TI42100600	PR130-18-I5.39S	TI42200600
0~1000	0~100	PR130-29-I5.37S	TI42101000	PR130-29-I5.39S	TI42201000

注: 需要了解更多数据和产品, 请联系我们
Note: For more information and products, please contact us