

EC115L-液压软管

Hydraulic hose



- 软管结构: 一层钢丝编织增强层, 合成橡胶内层, 黑色合成橡胶外层
- EN857 1SC
- 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
- 温度范围: -40°C~+100°C
- 适配接头: 一体式或两件式, 编织类扣压接头
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, black synthetic rubber outer layer
- EN857 1SC
- Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Temperature range: -40°C~+100°C
- Adapter: one-piece or two-piece, braided crimping connector

								#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6.4	12.2	22.5	90.0	75	0.18	EC115-04L	HH011504
8	5/16	7.9	13.6	21.5	86.0	85	0.20	EC115-05L	HH011505
10	3/8	9.5	15.5	18.0	72.0	90	0.26	EC115-06L	HH011506
12	1/2	12.7	19.0	16.0	64.0	130	0.34	EC115-08L	HH011508
16	5/8	15.9	22.4	13.0	52.0	150	0.42	EC115-10L	HH011510
20	3/4	19.0	25.8	10.5	42.0	180	0.50	EC115-12L	HH011512
25	1	25.4	33.4	8.8	35.2	230	0.74	EC115-16L	HH011516
32	1 1/4	31.8	41.5	6.3	25.2	210	0.99	EC115-20L	HH011520

EC215L-液压软管

Hydraulic hose



- 软管结构: 一层钢丝编织增强层, 合成橡胶内层, 黑色合成橡胶外层
- 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
- 适配接头: 一体式或两件式, 编织类扣压接头
- EN857 2SC
- 温度范围: -40°C~+100°C
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, black synthetic rubber outer layer
- Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Adapter: one-piece or two-piece, braided crimping connector
- EN857 2SC
- Temperature range: -40°C~+100°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6.4	13.2	40.0	160.0	50	0.28	EC215-04L	HH021504
8	5/16	7.9	15.0	35.0	140.0	55	0.33	EC215-05L	HH021505
10	3/8	9.5	17.1	33.0	132.0	65	0.41	EC215-06L	HH021506
12	1/2	12.7	20.7	27.5	110.0	90	0.57	EC215-08L	HH021508
16	5/8	15.9	23.8	25.0	100.0	100	0.68	EC215-10L	HH021510
20	3/4	19.0	27.7	21.5	86.0	120	0.81	EC215-12L	HH021512
25	1	25.4	35.5	16.5	66.0	150	1.17	EC215-16L	HH021516
32	1 1/4	31.8	43.6	12.5	50.0	250	1.56	EC215-20L	HH021520
40	1 1/2	38.1	50.7	10.0	40.0	300	1.81	EC215-24L	HH021524